KNG Energy, Inc.

419-424-3427

Service Installation Record for DOT Qualified Natural Gas Service Line Installers

Fax form to 419-424-3309 or email knartker@kngenergy.com. Form must be received before tap will be installed.

Section A.			ation Information		
Service Line Installers Name & Company Name					
Service Line Installers Telephone Number Customer Name			Date Service Line Installed Contact Name & Phone No. for Tie-In		
Service Address			Installation Type	□ Replaced □ Misc.*	
Total BTU Load			* Misc. Reason		
Customer Service Line (Valve Material	s to Meter) (C Size	Service Depth	Service Length	Continuous Run?	
□ Plastic □ Direct Burial				Y / N	
□ Steel □ Insert	□ 1 1/4"	Pipe Specifications (this section must be completed)			
		Pipe Manufactu	anufacturer		
Tracer wire Y / N	□ Other	Date Manufactu		Coil #	
Service Line Test:	Time	PSI/oz	Drop	Instrument	
Service line must be te	sted for a	minimum of 15			
OQ ID Number: Expiration Date:					
Qualified by (Name of Qualifying Agency):					
Signature of Service Line Installer***					
Section B.	Ris	er Installation In	n		
Riser Installed by: OQ ID Number:			Brand of Riser Connection to Pipe	Factory InstalledField Installed	
			*** Use only KNG approved risers.		
Signature of Riser and/or Mechanical Fitting Installer***					
Service Line Installation must comply with the following standards:					
1. Materials used in the installation must meet KNG's approved standards.					
2. 12 gauge solid tracer wire must be properly installed and checked for continuity across entire length.					
The wire must be wrapped around the bracket at house with an additional 5' to 8' of wire left on main side.					
 Service line must be installed at a minimum depth of 18 inches with an additional 5' of pipe on main side. Service lines may not be installed under any structures. 					
 Service lines may not be installed under any structures. Meter bar & riser must be properly supported. Avoid using CSST pipe through outside wall when possible. 					
6. Pre-fab setting must be purchased from KNG.					
7. Pre-fab setting must be at least 3' away from an ignition source					
8. Pre-fab setting cannot be located under any window or closer than 3' to any opening.					
 The connection between meter bar and internal piping MUST be painted. Meter and valve must be accessible and protected from damage. 					
11. Weak link must be used when directional drilling or anytime when pulling pipe or fittings through the ground.					
*** By signing this form, the installer attests that they installed or repaired and tested the service line and/or meter					
set in accordance with applicable codes and standards. The installer's signature further attests that:					
1. Installer is Operator Qualified in accordance with the requirements set forth in 49 CFR 192, Subpart N. This means that the installed have been evaluated by a KNG approved third party qualifier and has been deemed qualified to perform					
the various covered tasks associated with installation of natural gas service lines. (3 year re-qualification required)					
 Installer has been evaluated and qualified by a KNG approved third party qualifier to join plastic pipe utilizing mechanical couplings. (1 year re-qualification required) 					
 Employer administers a Drug & Alcohol Testing Program that meets the requirements of 49 CFR 199, including random testing. 					
The installer understands and agrees that by KNG setting the meter, KNG is not assuming nor accepting any responsibility or liability for the installation or repair work performed by the installer and that the installer remains solely responsible for any work performed other than setting the meter. Further, the installer agrees to indemnity, hold harmless and, if requested, defend KNG, its officers, employees and agents from and against any and all liabilities, costs, claims, demands, fines, penalties, suits, proceedings, actions and causes of action, including reasonable attorneys' fee, arising out of, or associated with, or related to the installation described herein.					
For office use only:					
Was steel line replaced KNG inspector's name:		/es no	Internal Pipe Conc	dition: Smooth Pitted revision date: 9/5/19	